

Quality & Lamel Facility

Lamel Facility



Quality Impression



Our Highest quality level lamellas for unique engineered flooring

- 4 sides defect free quality
- Small healthy knots up to approximately 10-12 mm.
- No Black knots, hearth, inbark, rouge and sapwood allowed.



Quality Impression



Specifications

Thickness in mm

3,3	4,4	6,4		
-----	-----	-----	--	--

Width in mm

150	170	200	215	230	250
-----	-----	-----	-----	-----	-----

Length in mm

2000	2200	2500	2750	3000
------	------	------	------	------

General information

Our lamellas are manufactured in our state-of-the-art facility in the Ukraine, equipped with the latest “Neva” technology. This enables us to produce highly accurate end-products. After production, our lamellas are stored in our climate-controlled warehouse in which we take special precautions such as plastic wrapping and bundle strengthening to ensure the safe shipment for all of our products. Although we have standard thickness and widths, of course we can also make your orders custom made.

Thickness: The tolerance regarding the thickness of our top layer is $\pm 0,2$ mm, some pieces can be slightly thicker.

Quality: The quality of 10% of the lamellas can slight differ.

Perfect quality, for high level engineered flooring

- Healy knots up to approximately 35 mm.
- Unhealy knots up to approximately 15 mm.
- No heart, inbark, rouge or sapwood allowed.



Quality Impression



Specifications

Thickness in mm

3,3	4,4	6,4		
-----	-----	-----	--	--

Width in mm

150	170	200	215	230	250
-----	-----	-----	-----	-----	-----

Length in mm

2000	2200	2500	2750	3000
------	------	------	------	------

General information

Our lamellas are manufactured in our state-of-the-art facility in the Ukraine, equipped with the latest "Neva" technology. This enables us to produce highly accurate end-products. After production, our lamellas are stored in our climate-controlled warehouse in which we take special precautions such as plastic wrapping and bundle strengthening to ensure the safe shipment for all of our products. Although we have standard thickness and widths, of course we can also make your orders custom made.

Thickness: The tolerance regarding the thickness of our top layer is $\pm 0,2$ mm, some pieces can be slightly thicker.

Quality: The quality of 10% of the lamellas can slightly differ.

Light rustic quality with a high percentage of higher-quality lamellas for natural engineered flooring.

- Healthy knots up to approximately 60 mm.
- Unhealthy knots up to approximately 35 mm.
- Some pieces contain closed hearth.
- In bark till ± 100 mm is allowed.
- Rouge and wormholes are not allowed.



Quality Impression



Specifications

Thickness in mm

3,3	4,4	6,4		
-----	-----	-----	--	--

Width in mm

150	170	200	215	230	250
-----	-----	-----	-----	-----	-----

Length in mm

2000	2200	2500	2750	3000
------	------	------	------	------

General information

Our lamellas are manufactured in our state-of-the-art facility in the Ukraine, equipped with the latest “Neva” technology. This enables us to produce highly accurate end-products. After production, our lamellas are stored in our climate-controlled warehouse in which we take special precautions such as plastic wrapping and bundle strengthening to ensure the safe shipment for all of our products. Although we have standard thickness and widths, of course we can also make your orders custom made.

Thickness: The tolerance regarding the thickness of our top layer is $\pm 0,2$ mm, some pieces can be slightly thicker.

Quality: The quality of 10% of the lamellas can slightly differ.